SAFETY DATA SHEET (SDS)



Jacquard Products
Manufactured by Rupert, Gibbon & Spider, Inc.
P.O. Box 425 | Healdsburg, CA 95448
800.442.0455 | Fax: 707.433.4906
www.jacquardproducts.com

Piñata Alcohol Ink (Standard Colors) & Claro Extender - Pg I

Revision Date: 04/23/2018

SECTION I - CHEMICAL, PRODUCT & COMPANY INFORMATION

Product Name:	PIÑATA ALCOHOL INK & CLARO EXTENDER	
Product Number/Code:	002-031 (STANDARD COLORS), JFC1001, JFC2001	
Recommended Use:	Ink & ink medium for hard surfaces	
Restrictions on use:	None known	
Manufacturer:	Rupert, Gibbon & Spider, Inc. 1147 Healdsburg Ave. Healdsburg, CA 95448 1-800-442-0455 / 707-433-9577	
Emergency Number:	ChemTel, Inc Contract #MIS9128344	
	North America: International: I-800-255-3924 I-813-248-0585	

SECTION 2 - HAZARD(S) IDENTIFICATION

GHS classification in accordance witl	1 29 CFR 1910 (OSHA HCS)		
Toxicological Data on Ingredients:			
Hazard Classification			
Physical Hazards:	Flammable liquids	Category 2	
Health Hazards:	Acute toxicity, oral	Category 4	
	Skin Irritant	Category 2	
	Eye Irritant	Category 2A	
Environmental Hazards:	Not classified		
Label Elements	'		
Pictogram:	<u>(!)</u>		
Signal Words:	DANGER, WARNING		
Hazard Statements-EU:	H225 Highly flammable liquid and vapo H302 Harmful if swallowed. H315 Causes skin irritation. H319 Causes serious eye irritation.	r.	

Precautionary Statements-EU: Prevention:	P210 Keep away from heat/sparks/open flames/hot surfaces No smoking.		
Trevention.	P233 Keep container tightly closed.		
	P240 Ground/bond container and receiving equipment.		
	P241 Use explosion-proof electrical/ventilating/lighting/equipment.		
	P242 Use only non-sparking tools.		
	P243 Take precautionary measures against static discharge.		
	P260 Do not breathe mist/vapors/spray.		
	P264 Wash thoroughly after handling.		
	P270 Do not eat, drink or smoke when using this product.		
	P280 Wear protective gloves/protective clothing/eye protection.		
Response:	P301+P312 If swallowed: Call a poison center/doctor if you feel unwell. P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting. P302+P352		
	P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.		
	P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.		
	P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 Immediately call a poison center/doctor. P321 Specific treatment (see product label).		
	P332+P313 IF SKIN irritation occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention. P362 Take off contaminated clothing and wash before reuse. P363 Wash contaminated clothing before reuse. P370+P378 In case of fire: Use for extinction: CO2, powder or water spray		
Storage:	P403+P235 Store in a well-ventilated place. Keep cool.		
Disposal:	P501 Dispose of contents/container in accordance with local/regional/national/international regulations.		
Hazard(s) not otherwise classified:	There are no other hazards not otherwise classified that have been identified.		

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

Chemical identity	Content in percent (%)*	CAS#
Ethanol	50-70%	64-17-5
2-(propyloxy)ethanol	10-20%	2807-30-9
propan-I-ol	<10%	71-23-8
isopropyl acetate	<10%	108-21-4
Basic yellow 37	≤ 5%	6358-36-7
Nitrocellulose, colloided, granular	≤ 5%	9004-70-0
Basic Blue 7	≤ 5%	2390-60-5
Propan-2-ol	≤ 5%	67-63-0

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret. For the wording of the listed Hazard Statements, refer to section 16.

SECTION 4 - FIRST AID MEASURES

Description of first aid measures:	
In the event of skin contact:	Immediately remove any clothing soiled by the product. Immediately wash with water and soap and rinse thoroughly. If skin irritation or rash occurs: Get medical advice/attention.
In the event of eye contact:	Remove contact lenses if worn. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
In the event of swallowing:	Rinse out mouth and then drink plenty of water. Do not induce vomiting; immediately call for medical help.
In the event of exposure by inhalation:	Supply fresh air; consult doctor in case of complaints. Provide oxygen treatment if affected person has difficulty breathing.
Most important symptoms and effects, acute and delayed:	Irritating to eyes and skin. Coughing, dizziness, if inhaled. Breathing difficulty. May cause gastrointestinal irritation if ingested. Nausea in case of ingestion. DANGER: Harmful if swallowed.
Indication of any immediate medical attention and special treatment needed:	Treat symptomatically.

SECTION 5 - FIREFIGHTING MEASURES

Suitable extinguishing media:	CO2, extinguishing powder or water spray. Fight larger fire with alcohol resistant foam.
Unsuitable extinguishing media:	Water stream
Special hazards arising from the substance or mixture:	Formation of toxic gases is possible during heating or in case of fire.
Advice for fire fighters:	Protective equipment: Wear self-contained respiratory protective device. Wear fully protective suit. Additional information: Eliminate all ignition sources if safe to do so. Cool endangered receptacles with water spray.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:	Ensure adequate ventilation. Use personal protective equipment as required. Keep away from ignition sources. Protect from heat
Methods and material for containment and clean up:	Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders). Dispose of the collected material according to regulations.
Environmental procedures:	Avoid release to the environment. Inform respective authorities in case of seepage into water course or sewage system.
Reference to other sections:	See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7 - HANDLING AND STORAGE

Precautions for safe handling:	Use only in well ventilated areas. Avoid splashes or spray in enclosed areas. Keep out of reach of children.
Information about protection against explosions and fires:	Highly flammable liquid and vapor. Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
Conditions for safe storage including any incompatibilities:	Requirements to be met by storerooms and receptacles: Avoid storage near extreme heat, ignition sources or open flame. Store in cool, dry conditions in well sealed receptacles. Information about storage in one common storage facility: Store away from foodstuffs. Store away from oxidizing agents. Further information about storage conditions: Store locked up.
Specific end use(s):	No relevant information available.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Components with limit values that	64-17-5	PEL (USA):	Long-term value: 1,900 mg/m³, 1,000 ppm
require monitoring at the workplace:	Ethanol:	REL (USA):	Long-term value: 1,900 mg/m³, 1,000 ppm
		EV (Canada):	Long-term value: 1,900 mg/m³, 1,000 ppm
		LMPE (Mexico):	Long-term value: 1000 ppm A3
	2807-30-9 2 (propyloxy) ethanol:	EV (Canada):	Long-term value: 110 mg/m³, 25 ppm Skin
	71-23-8	PEL (USA):	Long-term value: 500 mg/m³, 200 ppm
	propan-I-ol:	REL (USA):	Short-term value: 625 mg/m³, 250 ppm Long-term value: 500 mg/m³, 200 ppm Skin
		TLV (USA):	Long-term value: 246 mg/m³, 100 ppm
		EL (Canada):	Long-term value: 100 ppm
		EV (Canada):	Long-term value: 100 ppm
		LMPE (Mexico):	Long-term value: 100 ppm A4
	108-21-4 isopropyl acetate:	PEL (USA):	Long-term value: 950 mg/m³, 250 ppm
		TLV (USA):	Short-term value: NIC-626 mg/m³, NIC-150 ppr Long-term value: NIC-417 mg/m³, NIC-100 ppm
		EL (Canada):	Short-term value: 200 ppm Long-term value: 100 ppm
		EV (Canada):	Short-term value: 200 ppm Long-term value: 100 ppm
		LMPE (Mexico):	Short-term value: 200 ppm Long-term value: 100 ppm
	67-63-0	PEL (USA):	Long-term value: 980 mg/m³, 400 ppm
	Propan-2-ol:	REL (USA):	Short-term value: 1225 mg/m³, 500 ppm Long-term value: 980 mg/m³, 400 ppm
		TLV (USA):	Short-term value: 984 mg/m³, 400 ppm Long-term value: 492 mg/m³, 200 ppm BEI
		EL (Canada):	Short-term value: 400 ppm Long-term value: 200 ppm
		EV (Canada):	Short-term value: 400 ppm Long-term value: 200 ppm
		LMPE (Mexico):	Short-term value: 400 ppm Long-term value: 200 ppm A4, IBE
Ingredients with biological limit values:	67-63-0 Propan-2-ol:	BEI (USA):	40 mg/L Medium: urine Time: end of shift at end of workweek Parameter:Acetone (background, nonspecific)

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Individual protection measures, such a	s personal protective equipment:
General protective and hygienic measures:	The usual precautionary measures for handling chemicals should be followed. Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work. Do not eat, drink or smoke while using the product. Immediately remove all soiled and contaminated clothing. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with the eyes and skin.
Eye/face protection:	Safety glasses Follow relevant national guidelines concerning the use of protective eye wear.
Skin protection:	Protective work clothing
Hand protection:	Protective gloves The glove material has to be impermeable and resistant to the product/the substance/ the preparation.
Limitation and supervision of exposure into the environment:	No relevant information available.
Risk management measures:	No relevant information available.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

General information:	
Appearance and physical state:	Liquid
Color:	According to product specification.
Type of Odor:	Not determined
Odor threshold:	Not determined
Important health, safety and environmental in	formation:
Initial Boiling Point and Boiling Range:	>35°C (>95°F)
Melting Point/Freezing Point:	Not determined
Flammability Classification:	Not applicable
Flash Point:	14°C (57.2°F)
Auto-ignition Temperature:	Not determined
Decomposition Temperature:	Not determined
Flammability Limits (lower/upper):	Not determined
Evaporation rate:	Not determined
Vapor Pressure:	Not determined
Vapor Density (Air=I):	Not determined
Octanol/Water Partition Coefficient (log Pow):	Not determined
Specific Gravity:	Not determined
Bulk Density:	Not determined
Water Solubility:	Not miscible or difficult to mix.
pH:	Not determined
Viscosity (dynamic, kinematic):	Not determined
Explosive Properties:	Product is not explosive. However, formation of explosive air/ vapor mixtures are possible.
Oxidizing Properties:	Non-oxidizing
Molecular Formula:	Not determined
Molecular Weight:	Not determined
Relative Density:	Not determined

SECTION 10 - STABILITY AND REACTIVITY

Reactivity:	No relevant information available.
Stability:	Stable under normal temperatures and pressures.
Possibility of hazardous reactions:	Highly flammable liquid and vapor. Reacts violently with oxidizing agents. Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized. Toxic fumes may be released if heated above the decomposition point. Used empty containers may contain product gases which form explosive mixtures with air.
Conditions to avoid:	Excessive heat
Incompatible materials:	Oxidizers, strong bases, strong acids
Hazardous decomposition products (under fire conditions only):	Carbon monoxide, carbon dioxide, oxides of nitrogen and sulfur Chlorine compounds

SECTION 11 - TOXICOLOGICAL INFORMATION

Information on toxicological effects:		
Acute toxicity: Harmful if swallowed LD/LC50 values that are relevant for classification:		
64-17-5 Ethanol:	Oral: LD50 7,060 mg/kg (rat)	
	Inhalative: LC50/4h 20,000 mg/l (rat)	
2807-30-9 2-(propyloxy)ethanol:	Oral: LD50 2,260 mg/kg (mouse); 3,	
	Dermal: LD50 1,300 mg/kg (rabbit)	
2390-60-5 Basic Blue 7:	Oral: LD50 100 mg/kg (rat)	
	Dermal: LD50 >2,500 mg/kg (rabbit)	
6358-36-7 Basic yellow 37:	Oral: LD50 >50-300 mg/kg (rat)	
Primary irritant effects:		
Skin Contact:	Irritant to skin and mucous membranes.	
Eye Contact:	Causes eye irritation.	
Sensitization:	Based on available data, the classification criteria are not met.	
Carcinogenic categories:	1	
IARC (International Agency for Research on Cancer):	64-17-5 Ethanol I	I
	13463-67-7 titanium dioxide	2B
NTP (National Toxicology Program):	None of the ingredients are listed.	
OSHA-Ca (Occupational Safety & Health Administration):	None of the ingredients are listed.	
Possible routes of exposure:	Ingestion, inhalation, eye contact, skin contact.	
Germ cell mutagenicity:	Based on available data, the classification criteria are not met.	
Carcinogenicity:	Based on available data, the classification criteria are not met.	
Reproductive toxicity:	Based on available data, the classification criteria are not met.	
STOT-single exposure:	Based on available data, the classification criteria are not met.	
STOT-repeated exposure:	Based on available data, the classification criteria are not met.	
Aspiration hazard:	Based on available data, the classification criteria are not met.	

SECTION 12 - ECOLOGICAL INFORMATION

Toxicity:		
Aquatic toxicity:	Toxic to aquatic life with long lasting effects: 2390-60-5 Basic Blue 7 LC50 < I mg/I (daphnia)	
Persistence and degradability:	No relevant information available.	
Bioaccumulative potential:	No relevant information available.	
Mobility in soil:	No relevant information available.	
Other adverse effects:	No relevant information available.	
Additional information:	Avoid release to the environment. Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment cannot be excluded.	

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste treatment methods:	
Disposal:	The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and non-hazardous wastes.
Container Disposal:	Disposal must be made according to official regulations.

SECTION 14 - TRANSPORT INFORMATION

PACKING GROUP (DOT, ADR, IMDG, IATA):	2	
DOT:		
DOT Proper Shipping Description:	Printing Ink	
Hazard Class:	3	
Placard:	Flammable Liquids	
Marine Pollutant:	Yes - Product contains environmentally hazardous substances: Basic yellow 37, Basic Blue 7	
Transport/additional information:	Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each. Labeling as a Marine Pollutant is only required for bulk single package shipments. Bulk packaging consists of a maximum capacity of greater than 450 L (119 gallons) for a liquid and a maximum net mass greater than 400 kg (882 pounds) for a solid. (See 171.4(c)).	
IMDG:		
UN number:	UN1210	
UN proper shipping name:	Printing Ink	
Hazard Class:	3	
Placard:	Flammable Liquids	
EMS No.:	F-E, S-D	
Marine Pollutant:	Yes - Product contains environmentally hazardous substances: Basic yellow 37, Basic Blue 7	
Transport/additional information:	Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each. Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to provisions relevant to marine pollutants. (See 2.10.2.7)	
IATA:		
UN No:	UN1210	
Hazard Class:	3	
Packing group (DOT):	2	
Placard:	Flammable Liquids	
EMS No.:	F-E, S-D	
Transport/additional information:	Limited Quantity for packages less than 30 kg gross and inner packagings less than 0.5 L each /I L net.	
ADR:		
Hazard Class:	3 (F1) Flammable liquids	
Label:	3	
Transport/additional information:	Limited Quantity for packages less than 30kg gross and inner packagings less than 5 L each. Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to provisions relevant to marine pollutants (See 5.2.1.81.).	
Special precautions for user:		
Warning: Flammable Liquids		
Danger code (Kemler):	33	
EMS number:	F-E,-S-D	
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:	Not applicable	

SECTION 15 - REGULATORY INFORMATION

Hazard categories	
Section 302 (extremely hazardous substances):	None of the ingredients are listed.
Section 355 (extremely hazardous substances):	None of the ingredients are listed.
Section 313 (specific toxic chemical listings):	67-63-0 Propan-2-ol
TSCA (Toxic Substances Control Act):	All ingredients are listed.
Proposition 65 (California):	Used as directed, this product will NOT expose you to chemicals known to cause cancer.
	Ethanol - listing refers specifically to alcoholic beverage consumption and is not applicable for product. Reference to titanium dioxide is based on unbound respirable particles and is not generally applicable to product as supplied. 64-17-5 Ethanol 13463-67-7 titanium dioxide
Chemicals known to cause developmental toxicity for females:	None of the ingredients are listed.
Chemicals known to cause developmental toxicity for males:	None of the ingredients are listed.
Chemicals known to cause developmental toxicity:	Ethanol - listing refers specifically to alcoholic beverage consumption and is not applicable for product. 64-17-5 Ethanol
EPA (Environmental Protection Agency):	None of the ingredients are listed.
IARC (International Agency for Research on Cancer):	64-17-5 Ethanol 13463-67-7 titanium dioxide
NIOSH-Ca (National Institute for Occupational Safety and Health):	Present in trace quantities: 13463-67-7 titanium dioxide

SECTION 16 - OTHER INFORMATION

HMIS Hazard ID:	
Health:	No information available
Flammability:	No information available
Reactivity:	No information available
Hazard rating: 0 - Minimal; I - Slight; 2 - Moderate; 3 - Serious; 4 - Severe; *Chronic health effect	

Disclaimer:

The information contained in this SDS is based on data from sources considered to be reliable but Rupert, Gibbon & Spider, Inc. does not guarantee the accuracy or completeness thereof. Rupert, Gibbon & Spider, Inc. urges each customer or recipient of this SDS to study it carefully to become aware of and understand the hazards associated with this product. The reader should consider consulting reference works or individuals who are experts in ventilation, toxicology or fire and understand the data in this SDS.

Revision Date: 04/23/2018

National Chemical Inventories	*
All components of this product are	e listed on the following chemical substance inventories:TSCA (USA)
DSL	(Canada)
EINECS	(Europe)
ENCS	(Japan) ECL
	(Korea)
AICS	(Australia) NZIoC
	(New Zealand)
PICCS	(Philippines)
IECSC	(China)

ACGIH	American Conference of Governmental Industrial Hygienists
ADR	International carriage of Dangerous goods by Road
AICS	Australian Inventory of Chemical Substances
ATE	Acute Toxicity Estimate
BfR	Bundesinstitut für Risikobewertung recommendations for food contact materials
BCF	Bioconcentration Factor
BOD5	5-day Biochemical Oxygen Demand
CERCLA	Comprehensive Environmental Response, Compensation and Liability Act
CLP	Classification, Labeling and Packaging regulation
COD	Chemical Oxygen Demand DOT Department of Transportation DSL Domestic Substances List
EINECS	European Inventory of Existing Chemical Substances
ECL	Existing Chemicals List (Korea)
ENCS	Existing and New Chemical Substances Inventory (Japan)
EN 689	Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy.
ERG	Emergency Response Guide
GHS	Globally Harmonized System
HMIS	Hazardous Materials Information System IARC International Agency for Research on Cancer IATA International Air Transport Association
ICAO	International Civil Aviation Organization IDLH Immediately Dangerous to Life and Health IMDG International Maritime Dangerous Goods
LD50	Lethal Dose to 50% of test animal population
MAK	Maximale Arbeitsplatz Konzentration
NTP	National Toxicology Program
OEL	Occupational Exposure Limit
OSHA	Occupational Safety & Health Administration
PBT	Persistent, Bioaccumulative and Toxic vPvB Very Persistent and Very Bioaccumulative PEL Permissible exposure limit
PICCS	Philippine Inventory of Commercial Chemical Substances
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation and Authorization of Chemical Substances
RID	International carriage of dangerous goods by Rail SARA Superfund Amendments and Reauthorization Act STEL Short Term Exposure Limit
SVHC	Substance of Very High Concern
TLV	Threshold Limit Value
TSCA	Toxic Substances Control Act
TWA	Time Weighted Average
VOC	Volatile Organic Compound
WGK	Wassergefahrdungsklasse (Water Hazard Class) WHMIS Workplace Hazardous Material Identification System

SAFETY DATA SHEET (SDS)



Jacquard Products
Manufactured by Rupert, Gibbon & Spider, Inc.
P.O. Box 425 | Healdsburg, CA 95448
800.442.0455 | Fax: 707.433.4906
www.jacquardproducts.com

Piñata Alcohol Ink (Metallic Colors) & Clean Up Solution - Pg I

Revision Date: 09/26/2019

SECTION I - CHEMICAL, PRODUCT & COMPANY INFORMATION

Product Name:	PIÑATA ALCOHOL INK (METALLIC COLORS) & CLEAN UP SOLUTION	
Product Number/Code:	032-036, JFC1000, JFC2000	
Recommended Use:	Inks to color any hard surface; for clean up of alcohol inks.	
Restrictions on use:	None known	
Manufacturer:	Rupert, Gibbon & Spider, Inc. I 147 Healdsburg Ave. Healdsburg, CA 95448 I-800-442-0455 / 707-433-9577	
Emergency Number:	ChemTel, Inc Contract	#MIS9128344
	North America: I-800-255-3924	International: 1-813-248-0585

SECTION 2 - HAZARD(S) IDENTIFICATION

GHS classification in accordance wit	h 29 CFR 1910 (OSHA HCS)		
Toxicological Data on Ingredients:			
Hazard Classification			
Physical Hazards:	Flammable liquids	Category 2	
Health Hazards:	Serious eye damage/eye irritation	Category 2E	
Environmental Hazards:	Hazardous to the aquatic environment, chronic hazard Category 2		
Label Elements		·	
Pictogram:			
Signal Words:	Danger, Warning		
Hazard Statements-EU:	H225 Highly flammable liquid and vapor. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects.	H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.	

Prevention:	P201 Obtain special instructions before use.
	P202 Do not handle until all safety precautions have been read and understood.
	P210 Keep away from heat/sparks/open flames/hot surfaces. – No smoking
	P233 Keep container tightly closed.
	P240 Ground/bond container and receiving equipment.
	P241 Use explosion-proof electrical/ventilating/lighting/equipment.
	P242 Use only non-sparking tools.
	P243 Take precautionary measures against static discharge.
	P264 Wash hands thoroughly after handling.
	P273 Avoid release into the environment.
	P280 Wear protective gloves/protective clothing/eye protection/face
	protection.
	P281 Use personal protective equipment as required.
	P391 Collect spillage. Hazardous to the aquatic environment.
Response:	P303+P361+P353 IF ON SKIN (or hair): Remove/take off immediately all
	contaminated clothing. Rinse SKIN with water/shower.
	P305+P351+P338 IF IN EYES: Rinse cautiously with water for several
	minutes. Remove contact lenses, if present and easy to do. Continue
	rinsing.
	P308+P313 IF exposed or concerned: Get medical advice/attention.
	P337+P313 IF eye irritation persists: Get medical advice/attention.
	P370+P378 In case of fire: Use carbon dioxide or dry powder, alcohol resistant foam, water in large amounts.
Storage:	P403+P235 Store in a well-ventilated place. Keep cool.
•	P404 Store in a closed container.
	P405 Store locked up.
Disposal:	P501 Dispose of contents/container to an appropriate treatment and
,	disposal facility in accordance with applicable laws and regulations, and
	product characteristics at time of disposal.
Hazard(s) not otherwise classified:	Static accumulating flammable liquid can become electrostatically charged
. ,	even in bonded and grounded equipment. Sparks may ignite liquid and
	vapor. May cause flash fire or explosion. May cause skin and eye irritation.

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CLEAN UP SOLUTION		
Chemical identity	Content in percent (%)*	CAS#
Ethanol	>=85 - <=95%	64-17-5
Propyl acetate	>=0 - <=5%	109-60-4
Isopropyl Alcohol	>=0 - <=5%	67-63-0
METALLIC COLORS		
Chemical identity	Content in percent (%)*	CAS#
Ethanol	50 - 65%	64-17-5
Propyl acetate	0 - 3.25%	109-60-4
Isopropyl Alcohol	0 - 3.25%	67-63-0
Colored pigments (Rich Gold, Silver, Copper, Brass & Pearl)	5 - 15%	Proprietary
*All concentrations are percent by we	ight unless ingredient is a gas. Gas concentra	tions are in percent by volume.

^{*}All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume. Composition comments: The components are not hazardous or are below required disclosure limits.

SECTION 4 - FIRST AID MEASURES

Description of first aid measures:		
In the event of skin contact:	Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.	
In the event of eye contact:	If in eyes, hold eyes open, flood with water for at least 15 minutes and see a doctor.	
In the event of swallowing:	Rinse mouth. Do NOT induce vomiting. Never give liquid to an unconscious person. Get medical attention immediately.	
In the event of exposure by inhalation:	Move to fresh air. If breathing is difficult, give oxygen. Perform artificial respiration if breathing has stopped.	
Most important symptoms and effects, acute and delayed:	No data available	
Indication of any immediate medical attention and special treatment needed:	No data available	

SECTION 5 - FIREFIGHTING MEASURES

General fire hazards:	No data available
Suitable extinguishing media:	Use carbon dioxide or dry powder, alcohol resistant foam, water in large amounts.
Unsuitable extinguishing media:	No data available
Special hazards arising from the substance or mixture:	No data available
Special fire fighting procedures:	No data available
Special protective equipment for firefighters:	No data available

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:	No data available
Methods and material for containment and clean up:	Absorb spillage with non-combustible, absorbent material. Dike for later disposal. All equipment used when handling the product must be grounded. Eliminate sources of ignition.

SECTION 7 - HANDLING AND STORAGE

Precautions for safe handling:	Use personal protective equipment as required. Use only with adequate ventilation. Avoid breathing mists or vapors. Flammable/combustible - Keep away from oxidizers, heat and flames.
Conditions for safe storage including any incompatibilities:	No data available

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational expos	ure limits:		
Chemical identity	Туре	Exposure Limit Values	Source
Ethanol	STEL	1,000 ppm	US.ACGIH Threshold Limit Values (03 2013
	REL	I,000 ppm - I,900 mg/m ³	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	PEL	1,000 ppm - 1,900 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	1,000 ppm - 1,900 mg/m ³	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	1,000 ppm - 1,900 mg/m ³	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	ST ESL	1,910 μg/m³	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (02 2013)
	AN ESL	I,880 μg/m³	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (02 2013)
	AN ESL	1,000 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (02 2013)
	ST ESL	1,010 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (02 2013)
	TWA PEL	1,000 ppm - 1,900 mg/m ³	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (02 2012)
Propyl acetate	TWA	200 ppm	US.ACGIH Threshold Limit Values (03 2013
	STEL	250 ppm	US.ACGIH Threshold Limit Values (03 2013
	REL	200 ppm - 840 mg/m ³	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	250 ppm - 1,050 mg/m ³	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	PEL	200 ppm - 840 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	STEL	250 ppm - 1,050 mg/m ³	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	200 ppm - 840 mg/m ³	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	200 ppm - 840 mg/m ³	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	STEL	250 ppm - 1,050 mg/m ³	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	AN ESL	835 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (02 2013)
	ST ESL	I,000 μg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (02 2013)
	ST ESL	240 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (02 2013)
	AN ESL	200 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (02 2013)

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational exposure	e limits:		
Chemical identity	Туре	Exposure Limit Values	Source
Propyl acetate	TWA PEL	200 ppm - 840 mg/m ³	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (02 2012)
	STEL	250 ppm 1,050 mg/m ³	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (02 2012)
Isopropyl Alcohol	TWA	200 ppm	US.ACGIH Threshold Limit Values (03 2013)
	STEL	400 ppm	US.ACGIH Threshold Limit Values (03 2013)
	REL	400 ppm - 980 mg/m ³	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	500 ppm - 1,225 mg/m ³	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	PEL	400 ppm - 980 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	STEL	500 ppm - 1,225 mg/m ³	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	400 ppm - 980 mg/m ³	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	STEL	500 ppm - 1,225 mg/m ³	US.Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	TWA	400 ppm - 980 mg/m ³	US.Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	ST ESL	4,920 µg/m³	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (02 2013)
	AN ESL	492 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (02 2013)
	ST ESL	2,000 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (02 2013)
	AN ESL	200 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (02 2013)
	TWA PEL	400 ppm - 980 mg/m ³	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (02 2012)
	STEL	500 ppm - 1,225 mg/m ³	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (02 2012)
Biological limit values:			
Chemical identity:		Exposure Limit Values:	Source
Isopropyl Alcohol (acetorat end of work week)	ne: sampling time: end of shift	40 mg/l (urine)	ACGIH BEL (03 2013)
Appropriate engineering controls:		No data available	·
Individual protection mea	asures, such as personal protec	tive equipment:	
General information:		No data available	
Eye/face protection:		No data available	
Skin/hand protection:		No data available	
Respiratory protection:		No data available	
Hygiene measures:		No data available	

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

General information:		
Appearance and physical state:	Liquid	
Color:	No data available	
Type of Odor:	No data available	
Odor threshold:	No data available	
Important health, safety and environmental in	formation:	
Initial Boiling Point and Boiling Range:	167-217°F / 75-103°C	
Melting Point/Freezing Point:	No data available	
Flammability Classification:	No data available	
Flash Point:	40°F / 4°C	
Auto-ignition Temperature:	No data available	
Decomposition Temperature:	No data available	
Flammability Limits (lower/upper):	No data available	
Evaporation rate:	No data available	
Vapor Pressure:	No data available	
Vapor Density (Air=I):	No data available	
Octanol/Water Partition Coefficient (log Pow):	No data available	
Specific Gravity:	No data available	
Bulk Density:	No data available	
Water Solubility:	No data available	
pH:	No data available	
Viscosity:	No data available	
Explosive Properties:	No data available	
Oxidizing Properties:	No data available	
Molecular Formula:	No data available	
Molecular Weight:	No data available	
Relative Density:	No data available	

SECTION 10 - STABILITY AND REACTIVITY

Reactivity:	No data available
Stability:	No data available
Possibility of hazardous reactions:	No data available
Conditions to avoid:	No data available
Incompatible materials:	No data available
Hazardous decomposition products:	No data available

SECTION 11 - TOXICOLOGICAL INFORMATION

Acute Oral Toxicity:	ATEmix (): 3,457.202505 mg/kg
Acute Dermal Toxicity:	Not classified for acute toxicity based on available data.
Acute Inhalation Toxicity:	No data available Specified substance: Ethanol LC50 (Rat, 10 h): 20,000 mg/l LC50 (Mouse, 4 h): 39 mg/l LC50 (Cat,): 85.41 mg/l 2 (reliable with restrictions) LC50 (Rat,): 130.7 mg/l (, No) 2 (reliable with restrictions) LC50 (Mouse,): > 38 mg/l 4 (not assignable)
Repeated dose toxicity:	No data available
Skin Corrosion/Irritation:	No data available
Serious Eye Damage / Eye Irritation:	No data available Specified substance: Propyl acetate Concentration of 200 ppm causes irritation of eyes.
Respiratory or Skin Sensitization:	No data available
Germ Cell Mutagenicity:	In vitro: No data available In vivo: No data available
Carcinogenicity:	IARC Monographs on the Evaluation of Carcinogenic Risks to Humans: Ethanol: Overall evaluation I. Carcinogenic to humans (when taken orally as a beverage; therefore does not apply to this product).
	US. National Toxicology Program (NTP) Report on Carcinogens: Ethanol: Known to be Human Carcinogen (when taken orally as a beverage therefore does not apply to this product).
	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): No carcinogenic components identified.
Reproductive Toxicity:	No data available
Specific Target Organ Toxicity - single exposure (STOT-se):	No data available
Specific Target Organ Toxicity - repeated exposure (STOT-re):	No data available
Aspiration Hazard:	No data available
Potential Health Effects:	
Skin Contact:	No data available
Eye Contact:	No data available
Ingestion:	No data available
Inhalation:	No data available
Other effects:	No data available

SECTION 12 - ECOLOGICAL INFORMATION

Toxicity:	
Acute/prolonged toxicity to fish:	Specified substance: Ethanol LC50 (Fathead minnow (Pimephales promelas), I h): > 18,000 mg/l Mortality LC50 (Zebra danio (Danio rerio), 2 h): > 100 mg/l Mortality LC50 (Zebra danio (Danio rerio), 2 h): > 100 mg/l Mortality LC50 (Rainbow trout, donaldson trout (Oncorhynchus mykiss), 4 d): 42 mg/l Mortality LC50 (Zebra danio (Danio rerio), 4 h): > 100 mg/l Mortality
	Specified substance: Propyl acetate LC50 (Fathead minnow (Pimephales promelas), 24 h): 70 mg/l Mortality LC50 (Fathead minnow (Pimephales promelas), 48 h): 66 mg/l Mortality LC50 (Fathead minnow (Pimephales promelas), 96 h): 56 - 64 mg/l Mortality LC50 (Carp (Leuciscus idus melanotus), 48 h): 194 mg/l Mortality LC50 (Carp (Leuciscus idus melanotus), 48 h): 97 mg/l Mortality
	Specified substance: Isopropyl Alcohol LC50 (Fathead minnow (Pimephales promelas), 1 h): 11,830 mg/l Mortality LC50 (Fathead minnow (Pimephales promelas), 24 h): 10,600 mg/l Mortality LC50 (Fathead minnow (Pimephales promelas), 24 h): 11,160 mg/l Mortality LC50 (Harlequinfish, red rasbora (Rasbora heteromorpha), 24 h): 7,100 mg/l Mortality LC50 (Bluegill (Lepomis macrochirus), 24 h): >1,400 mg/l Mortality
Acute/prolonged toxicity to aquatic invertebrates:	Specified substance: Ethanol LC50 (Water flea (Daphnia magna), 216 h): 232 - 814 mg/l Mortality LC50 (Water flea (Ceriodaphnia dubia), 240 h): 1,284 - 2,638 mg/l Mortality LC50 (Water flea (Daphnia magna), 48 h): 12,813 - 15,804 mg/l Mortality LC50 (Brine shrimp (Artemia franchiscana), 48 h): 25.5 mg/l Mortality LC50 (Water flea (Ceriodaphnia dubia), 48 h): 3,046 - 4,432 mg/l Mortality
	Specified substance: Propyl acetate LC50 (Water flea (Daphnia magna), 24 h): 511 mg/l Mortality LC50 (Brine shrimp (Artemia salina), 24 h): 820 mg/l Mortality
	Specified substance: Isopropyl Alcohol LC50 (Water flea (Daphnia magna), 24 h): > 10,000 mg/l Mortality LC50 (Common shrimp, sand shrimp (Crangon crangon), 48 h): 900 - 1,950 mg/l Mortality LC50 (Common shrimp, sand shrimp (Crangon crangon), 96 h): 750 - 1,650 mg/l Mortality LC50 (Brine shrimp (Artemia salina), 24 h): >10,000 mg/l Mortality
Chronic toxicity to the aquatic environment (fish, aquatic invertebrates, aquatic plants):	No data available
Persistence and degradability:	No data available
BOD/COD ratio:	No data available
Bioaccumulative potential:	Bioconcentration factor (BCF): No data available
Partition coefficient n-octanol/water (log Kow):	Ethanol: -0.31 / Propyl acetate: 1.23 / Isopropyl Alcohol: 0.05
Mobility in soil:	No data available
Known or predicted distribution to environmental compartments (Ethanol, Propyl acetate, Propan-2-ol):	No data available

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste treatment methods:		
Disposal:		No data available
	Container Disposal:	No data available

SECTION 14 - TRANSPORT INFORMATION

DOT:	
UN number:	UN 1170
DOT Proper Shipping Description:	Ethanol
Hazard Class:	3
Placard:	3
Packing group:	II
Marine Pollutant:	Not regulated

SECTION 15 - REGULATORY INFORMATION

Safety, health and envir	onmental regulations/legi	slation specific for the sub	stance or mixture:
Hazard categories			
US Federal Regulations	:		
US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):		None present or none present in regulated quantities.	
CERCLA Hazardous Substance List (40 CFR 302.4):		Chemical identity:	Regulated Quantity:
		Ethanol	100 lbs.
		Propyl acetate	100 lbs.
		Isopropyl Alcohol:	100 lbs.
Superfund amendments and reauthorization act of 1986 (SARA) Hazard categories:		Not listed	
SARA 302 Extremely hazardous substance:		None present or none present in regulated quantities.	
SARA 304 Emergency	SARA 304 Emergency release notification:		RQ:
		Ethanol	100 lbs.
		Propyl acetate	100 lbs.
		Isopropyl Alcohol:	100 lbs.
SARA 311/312 Hazard	dous chemical:	Chemical identity:	Threshold Planning Quantity:
		Ethanol	100 lbs.
		Propyl acetate	100 lbs.
		Isopropyl Alcohol:	100 lbs.
SARA 313 (TRI repor	ting):		
Chemical identity:	Reporting threshold for other users:	Reporting threshold for manufacturing and processing:	
Isopropyl Alcohol	10,000 lbs.	25,000 lbs.	
Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3):		None present or none present in regulated quantities.	
Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):		None present or none present in regulated quantities.	

SECTION 15 - REGULATORY INFORMATION

US. California Proposition 65:	Used as directed, this product will NOT expose you to chemicals know to cause cancer.	
	Ethanol:	Carcinogenic (when taken orally as a beverage; therefore does not apply to this product)
	Ethanol:	Developmental toxin (when taken orally as a beverage; therefore does not apply to this product)
	NOTE: Ethanol - listing refers specifically to alcoholic beverage consumption and is not applicable for product.	
US. New Jersey Worker and Community Right-to-	Ethanol:	Listed
Know Act:	Propyl acetate:	Listed
	Isopropyl Alcohol:	Listed
US. Massachusetts RTK - Substance List:	Ethanol:	Listed
	Propyl acetate:	Listed
US. Pennsylvania RTK - Hazardous Substances:	Ethanol:	Listed
	Propyl acetate:	Listed
US. Rhode Island RTK:	No ingredient regulated by RI Right-to-Know Law present.	
Inventory status:		
Canada DSL Inventory List: Not in compliance with the inventory.		e inventory.
EU EINECS List:	Not in compliance with the inventory.	
EU ELINCS List:		
Japan (ENCS) List:	Not in compliance with the inventory.	
EU No Longer Polymers List:	Not in compliance with the inventory.	
China Inv. Existing Chemical Substances:	Not in compliance with the inventory.	
Korea Existing Chemicals Inv. (KECI):	Not in compliance with the inventory.	
Canada NDSL Inventory:	Not in compliance with the inventory.	
Philippines PICCS:	Not in compliance with the inventory.	
USTSCA Inventory:	On or in compliance with the inventory.	
New Zealand Inventory of Chemicals:	Not in compliance with the	e inventory.
Japan ISHL Listing:	Not in compliance with the	inventory

SECTION 16 - OTHER INFORMATION

HMIS Hazard ID:		
Health:	*	
Flammability:	3	
Reactivity:	0	
Personal Protection:	K (Hood, Gloves, Protective Suit & Boots)	
Hazard rating: 0 - Minimal; 1 - Slight; 2 - Moderate; 3 - Serious; 4 - Severe; *Chronic health effect		

Disclaimer:

The information contained in this SDS is based on data from sources considered to be reliable but Rupert, Gibbon & Spider, Inc. does not guarantee the accuracy or completeness thereof. Rupert, Gibbon & Spider, Inc. urges each customer or recipient of this SDS to study it carefully to become aware of and understand the hazards associated with this product. The reader should consider consulting reference works or individuals who are experts in ventilation, toxicology or fire and understand the data in this SDS.

Revision Date: 09/26/2019

ACGIH	American Conference of Governmental Industrial Hygienists		
ADR	International carriage of Dangerous goods by Road		
AICS	Australian Inventory of Chemical Substances		
ATE	Acute Toxicity Estimate		
BfR	Bundesinstitut für Risikobewertung recommendations for food contact materials		
BCF	Bioconcentration Factor		
BOD5	5-day Biochemical Oxygen Demand		
CERCLA	Comprehensive Environmental Response, Compensation and Liability Act		
CLP	Classification, Labeling and Packaging regulation		
COD	Chemical Oxygen Demand DOT Department of Transportation DSL Domestic Substances List		
EINECS	European Inventory of Existing Chemical Substances		
ECL	Existing Chemicals List (Korea)		
ENCS	Existing and New Chemical Substances Inventory (Japan)		
EN 689	Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy.		
ERG	Emergency Response Guide		
GHS	Globally Harmonized System		
HMIS	Hazardous Materials Information System IARC International Agency for Research on Cancer IATA International Air Transport Association		
ICAO	International Civil Aviation Organization IDLH Immediately Dangerous to Life and Health IMDG International Maritime Dangerous Goods		
LD50	Lethal Dose to 50% of test animal population		
MAK	Maximale Arbeitsplatz Konzentration		
NTP	National Toxicology Program		
OEL	Occupational Exposure Limit		
OSHA	Occupational Safety & Health Administration		
PBT	Persistent, Bioaccumulative and Toxic vPvB Very Persistent and Very Bioaccumulative PEL Permissible exposure limit		
PICCS	Philippine Inventory of Commercial Chemical Substances		
PNEC	Predicted No Effect Concentration		
REACH	Registration, Evaluation and Authorization of Chemical Substances		
RID	International carriage of dangerous goods by Rail SARA Superfund Amendments and Reauthorization Act STEL Short Term Exposure Limit		
SVHC	Substance of Very High Concern		
TLV	Threshold Limit Value		
TSCA	Toxic Substances Control Act		
TWA	Time Weighted Average		
VOC	Volatile Organic Compound		
WGK	Wassergefahrdungsklasse (Water Hazard Class) WHMIS Workplace Hazardous Material Identification System		